

Comparison

Overview of features

Each Melitta® CAFFEO® model range has its own unique features. The table below helps you to get a quick overview.



Technical characteristics	CAFFEO® CI®	CAFFEO® Gourmet	CAFFEO® BISTRO	CAFFEO® LATTEA®	CAFFEO® SOLO® & milk	CAFFEO® SOLO®
Adjustable brewing temperature	3 positions	3 positions	3 positions	3 positions	3 positions	3 positions
Continuously adjustable flow regulator for coffee	30–220 ml	30–220 ml	30–220 ml	30–220 ml	30–220 ml	30–220 ml
Pre-brewing function	•	•	•	•	•	•
Integrated hot water outlet	•	•	•	•	—	—
Coffee outlet for 1 or 2 cups	•	•	•	•	•	•
All-in-one outlet for 2 coffee/milk specialties at the same time	•	—	—	—	—	—
Height-adjustable coffee outlet	140 mm	130 mm	130 mm	135 mm	135 mm	135 mm
Premium stainless steel grinder	•	•	•	•	•	•
Grinding fineness	3 positions	3 positions	3 positions	3 positions	3 positions	3 positions
Ground coffee chute	•	•	•	—	—	—
Automatic regulation of ground coffee quantity	•	•	•	•	•	•
2-chamber bean container	•	•	•	—	—	—
Capacity of bean container	270 g (2 x 135 g)	270 g (2 x 135 g)	270 g (2 x 135 g)	125 g	125 g	125 g
Programmable coffee strength	4 positions	5 positions	4 positions	3 positions	3 positions	3 positions
Noise reduction	•	—	—	—	—	—
Milk froth system	One-Touch Venturi-System	Perfect Cappuccino® steam nozzle	Perfect Cappuccino® steam nozzle	Milk2Shower®	Panarello	—
External milk container	1 l	—	—	—	—	—
LED cup illumination	•	—	—	—	—	—
Display	LCD-text	LCD-text	LED symbol	LED symbol	LED symbol	LED symbol
Programmable dispensing button	•	•	•	—	—	—
My coffee function	•	—	—	—	—	—
Original preparation process for cappuccino	•	—	—	—	—	—
Stainless steel drip tray	•	•	•	•	•	•
Cup warming plate (passive)	•	•	•	•	•	•
Automatic cleaning and descaling programme	•	•	•	•	•	•
Removable brewing unit	•	•	•	•	•	•
Capacity of water container	1,8 l	1,8 l	1,8 l	1,2 l	1,2 l	1,2 l
Presetting of water hardness (4 positions)	•	•	•	•	•	•
Compatible with Claris® water filter	•	•	•	•	•	•
Automatic indication for changing water filter	•	•	•	•	•	•
Auto OFF function	•	•	—	•	•	•
0 watt button	•	•	—	•	•	•
Stand-by function	—	—	•	—	—	—
Energy-saving-mode (50% less current consumption)	•	•	•	•	•	•
Pump pressure	15 bar	15 bar	15 bar	15 bar	15 bar	15 bar
Cable rewind facility	•	•	•	•	•	•
Length of cable	ca. 1,1 m	ca. 1,1 m	ca. 1,1 m	ca. 1,1 m	ca. 1,1 m	ca. 1,1 m
Wattage	max. 1400 W	max. 1500 W	max. 1500 W	max. 1400 W	max. 1400 W	max. 1400 W
Voltage	220–240 V	220–240 V	220–240 V	220–240 V	220–240 V	220–240 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
Weight of device	ca. 9,3 kg	ca. 8,7 kg	ca. 8,7 kg	ca. 8,3 kg	ca. 8,3 kg	ca. 8,3 kg
Dimensions: (Height x Width x Depth in mm)	352 x 255 x 473	354 x 274 x 475	354 x 274 x 475	325 x 200 x 455	325 x 200 x 455	325 x 200 x 455

